#### S Ρ Ε С S Η Ε С F Α Т Ī 0 Ν Ξ I Ī Т



Model: 40812





# **Two Handle Laundry Faucet**

#### DESCRIPTION

- Metal construction with chrome plated finish
- 1/2" IPS connections
- 9" spout reach
- Accepts adaptor for seal trap primer (not included)
- · Includes both stream straightener and garden hose adaptor
- Six (6) individual boxes per master carton
- Handles withstand aggressive scrubbing cleaners

### **OPERATION**

- Lever-style handles
- · Hot side: Turn counterclockwise to open (clockwise to close)
- Cold side: Turn clockwise to open (counterclockwise to close)
- Will operate with less than 5 lbs. of torque
- No grasping motion required to operate the faucet handles

#### FLOW

· Meets the minimum spout flow is limited to 1.5 gpm (5.6 L/min) at 60 psi

## CARTRIDGE

- Ceramic disc technology
- · Non-metallic, non-ferrous, and brass material
- Single body construction for easy replacement

#### **STANDARDS**

- Third party certified to CSA B125, ASME A112.18.1, ANSI A117.1, ANSI/NSF 61/9, IAPMO, and all applicable requirements referenced therein, the Federal Safe Drinking Water Act, California Proposition 65, Illinois, Massachusetts, and Texas
- All CFG products are compliant to all plumbing codes that require 3rd party certification to the applicable plumbing/fitting standards
- · Features red/blue hot/cold temperature indicators

#### WARRANTY - RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- · Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

CFG-SS-40812-Rev. 11/14