

DA 6498 W Pure

Wall ventilation hood

with energy-efficient LED lighting and touch controls for simple operation.



- Lots of headroom – 35 1/2 (899)Inch wide with an exclusive glass design
- Unique user convenience – Con@ctivity
- Energy-efficient and quiet
- Safe and easy to clean - Miele CleanCover

EAN: 4002515961513 / material number: 10811940

Construction type	
Wall ventilation hood	•
Design	
Color	Graphite grey
Edge extraction	•
Operating modes	
Recirculated mode	Convertible
Control panel	
Electronic controls	•
Touch controls on glass	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
Cleaning convenience	
EasyClean CleanCover hood liner	•
Networking of domestic appliances	
WiFiConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
Filter system	
Dishwasher-safe stainless steel grease filters	1
Lighting	
LED ClearView lighting	•
Light intensity in Lx	440
Color temperature in K	3,500
Light dimmer function	•
Blower	
Dual-action blower	•
AC motor	•
Air throughput with max. duct diameter in vented mode (not for external version)	
Air throughput	Values upon request
Safety	
Safety shut-off	•
Single-ply safety glass (ESG)	•
Technical data	
Overall hood height for vented and external in in.(mm)	21 3/4 (550)
Overall hood height for recirculation in in.(mm)	21 3/4 (550)
Canopy width in in.(mm)	35 1/2 (899)
Height of hood canopy in in.(mm)	21 3/4 (550)
Depth of hood canopy in in.(mm)	20 7/8 (530)
Net weight in lbs. (kg)	56 (25.0)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•
Hard-wired	•
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1

more information:
<http://www.mieleusa.com/domestic>

For further information please see next page...

DA 6498 W Pure

Wall ventilation hood

with energy-efficient LED lighting and touch controls for simple operation.



Installation notes	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Non-return flap	•
Wireless stick Con@ctivity 2.0 for KM	XKS 3000 Z