

Project:		
Fixture Type:		
Location:		
Contact:		



Ceiling mounted • Dry location listed



Description:

Five-blade 52" Vox Hugger ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefits. A shatterproof, white opal shade contains a 17W dimmable, 3000K LED module. A remote control with batteries is included. The fan mounts close to the ceiling. Can be used to comply with California Title 20.

P2572-3030K

Images:

Specifications:

- · White (-30) (Painted)
- · Steel construction
- · Etched opal glass Diffuser
- A shatterproof, white opal shade contains a 17W dimmable, 3000K LED module with 90CRI and 1400 lumens
- · Indoor celling fan ideal for rooms with low ceiling heights
- · Features White blades and a White finish
- · Vox hugger fan mounts close to the ceiling only
- A full function hand held remote control with fan speed control, including reverse, and full range light dimming is included and comes with a convenient wall bracket for storage
- · Features modern styling for contemporary living spaces
- Reversible motor for year round comfort allows you to choose either a down drafts (summer) or an up draft (winter)
- Remote control may be replaced by a P2630-30 wall control
- · As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- · UL Dry location listed and rated for indoor use
- Can be used to comply with California Title 20.
- High Speed Energy Information: Airflow- 4276 cfm, Energy consumption- 62 watts (excluding lights), Airflow efficiency- 68 cfm/watt
- Canopy covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- 80" of wire supplied
- · White blades, plywood construction
- · 12 degree blade pitch
- · Full Function Remote Included
- · Meets Colifornia Title 24 JA8 2016



Dimensions:

Diameter: 52" Height: 11-5/8"

Glass

Width: 9-9/16" Height: 2-3/8"

Performance:

Number of Modules	1	
Input Power	18w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW	1386/77 (LM-79)	
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	50,000 (L70/TM-21)	
EMI/RFI	Title 20	
Min. Start Temp	-10 °C	
Max. Operating Temp	40 °C	
Warranty	Limited Lifetime warranty	
Labels	UL Dry location listed	
	Meets Colifornia Title 24 - JA8 - 2016	

